



Adobe AIR SDK Release Notes

Version	51.4.1.1
Date	17 September 2026
Document ID	HCS19-000287
Owner	Andrew Frost

Table of contents

1	Release Overview	3
1.1	Key changes.....	3
1.2	Deployment	3
1.3	Limitations	3
1.4	Feedback	4
1.5	Notes	4
2	Release Information	5
2.1	Delivery Method	5
2.2	The Content of the Release	5
2.3	AIR for Linux – Restrictions	6
2.4	AIR for Flex users.....	6
3	Summary of changes	7
3.1	Runtime and namespace version	7
3.2	Build Tools.....	7
3.3	AS3 APIs	7
3.4	Features	7
3.5	Bug Fixes	9
4	Configuration File.....	12
5	Android builds	16
5.1	AAB Target.....	16
5.2	Play Asset Delivery	16
5.3	Android Text Rendering	17
5.4	Android File System Access.....	18
6	Windows builds	20
7	MacOS builds.....	21
8	iOS support.....	22
8.1	32-bit vs 64-bit.....	22
8.2	MacOS remote linking from Windows	22
9	Splash Screens.....	25
9.1	Desktop (Windows/macOS)	25
9.2	Android	25
9.3	iOS	25
10	AIR Diagnostics.....	26
10.1	Purpose	26
10.2	Mechanism	26
10.3	Categories	26
10.4	Diagnostic API and guide	27
10.5	FAQs	27

1 Release Overview

Release 51.4.4.1 has been issued to address new requirements from the Apple and Android, notably the iOS requirement for using the scene lifecycle (applications that purport to be built using iPhoneOS SDK version 27 must use this, otherwise they will not start). On Android, it is now possible to enable the 'minify' and obfuscation tool which may help to meet future Play Store requirements.

1.1 Key changes

The iOS runtime has been significantly updated in order to move away from the original "MainWindow" xib file approach to the UI framework. Instead this now uses a storyboard file and has been configured to also support the scene lifecycle, with a single scene used for the whole AIR application. These changes have required the minimum supported iOS version to be updated to 13.0 (and it appears the App Store requirements will mean this needs to be updated to 15.0 before the spring of 2027).

On Android, the forthcoming requirements for obfuscation levels means there is now an opt-in flag to allow the minification and obfuscation of the Java code. Due to the requirements imposed by reflection and by the AIR use of JNI, a lot of the code cannot actually be obfuscated without breaking functionality, hence this may have limited effect. The rules files may need to be streamlined to try to improve the metrics but it's likely that the inclusion of ANEs will also impact these.

A number of bug fixes have also been included for Windows and macOS.

For further details, please see sections 3.4 and 3.5.1.

1.2 Deployment

To obtain the release, developers will need to install the AIR SDK Manager, available from the <https://airsdk.dev> website, as part of the "getting started" instructions, or directly from GitHub at: <https://github.com/airsdk/airsdkmanager-releases>

For Flex developers, once an AIR SDK has been downloaded, it can be merged onto an existing Flex (or Flex+AIR) SDK folder using the AIR SDK Manager – click on the cog icon on the right of an installed SDK and select "Flex SDK Overlay".

1.3 Limitations

For macOS users on 10.15+, the SDK may not work properly unless the quarantine setting is removed from the SDK: `$ xattr -d -r com.apple.quarantine /path/to/SDK`

Please note that there is no longer support for 32-bit IPA files, all IPAs will use just 64-bit binaries now so older iPhones/iPads may not be supported.

Android development should now be performed with an installation of Android Studio and the SDK and build tools, so that the new build mechanism (using Gradle and the Android Gradle Plug-in) can use the same set-up as Android Studio.

Linux runtimes are built using Ubuntu 16 for x86_64 variants in order to provide maximum compatibility; however, for arm64, the build environment uses Ubuntu 22 which then restricts usage to similar versions of Linux (i.e. that have glibc version 2.34 or later).

Note that ANGLE support on Windows, and H.264/AAC support on Linux using FFMEG, are both features that are currently causing significant issues and instabilities, and should only be used if a particular app has been tested sufficiently on all the target platforms.

1.4 Feedback

Any issues found with the SDK should be reported to adobe.support@wipro.com or preferably raised on <https://github.com/airsdk/Adobe-Runtime-Support/issues>.

The website for AIR SDK is available at: <https://airsdk.harman.com> with the developer portal available under <https://airsdk.dev>

1.5 Notes

Contributors to the <https://airsdk.dev> website would be very welcomed: this portal is being built up as the repository of knowledge for AIR and will be taking over from Adobe's developer websites

The AS3 documentation for AIR is updated and now also available under this site:
<https://airsdk.dev/reference/actionscript/3.0/>

We will continue to provide the shared AIR runtime for Windows/macOS; however, this is not a recommended deployment mechanism, it is preferably to create native installers based on the "bundle" deployments.

On MacOS in particular, the use of the shared AIR runtime to 'install' a .air file will not create a signed application – unless the new "air4mac" mechanism is used (see AIR-4887) – which means new MacOS versions may block these from running. To ensure a properly signed MacOS application is created, we still recommend using the "bundle" option with native code-signing options (i.e. those appearing after the "-target bundle" option) having a KeychainStore type with the alias being the full Developer ID certificate name.

2 Release Information

2.1 Delivery Method

The 51.3 releases will only be available via the AIR SDK Manager. The latest version of this can be downloaded from <https://github.com/airsdk/airsdkmanager-releases/releases>.

2.2 The Content of the Release

2.2.1 Detailed SW Content of the Release

Component Name	51.4.1.1
Core Tools	3.7.0
AIR Tools	3.1.2
Windows platform package	3.7.0
MacOS platform package	3.7.0
Linux platform package	3.7.0
Android platform package	3.7.0
iPhone platform package	3.7.0

2.2.2 Delivered Documentation

Title	Document Number	Version
Adobe AIR SDK Release Notes	HCS19-000287	51.4.1

2.2.3 Build Environment

Platform	Build Details
Android	Target SDK Version: 36 Minimum SDK Version: 21 Platform Tools: 28.0.3 Build Tools: 36.0.0 SDK Platform: Android-36 Note – these are the versions we use to build the AIR SDK and runtime, not the versions that will be generated or used by applications created by the AIR Developer Tool.
iOS	iPhoneOS SDK Version: 26.5 iPhoneSimulator SDK Version: 26.5 Xcode Version: 26.5 Minimum iOS Target: 13.0

tvOS	tvOS SDK Version:	26.5
	tvSimulator SDK Version:	26.5
	Xcode Version:	26.5
	Minimum tvOS Target:	13.0
MacOS	MacOS SDK Version:	26.5
	Xcode Version:	26.5
	Minimum macOS Target:	10.13
Windows	Visual Studio Version:	14.0.25431.01 Update 3
Linux	GCC Version	5.4.0 (Ubuntu 16.04.1 – x86_64) 11.4.0 (Ubuntu 22.04.3 – arm64)

2.3 AIR for Linux – Restrictions

The AIR SDK now supports both x86_64 and arm64 based Linux platforms. These are only available to developers with a commercial license to the SDK, and have some restrictions:

- No “shared runtime” support: applications would need to be built as ‘bundle’ packages with the captive runtimes
- Packaging into native installers (“native” target type for .deb or .rpm files) is currently not working: please create a “bundle” target and use Linux tools to distribute these
- No “StageWebView” component.

2.4 AIR for Flex users

HARMAN have continued Adobe’s strategy of issuing two AIR SDKs per platform: the first of these (“AIRSDK_[os].zip”) contains the newer ActionScript compiler and is a full, self-contained SDK for compiling and packaging AIR applications. The second of these is for combination with the Flex SDK (“AIRSDK_Flex_[os].zip”) which doesn’t include a number of the files necessary for ActionScript/MXML compilation. These SDKs should be extracted over the top of an existing, valid Flex SDK.

The original instructions from Adobe are at <https://helpx.adobe.com/uk/x-productkb/multi/how-overlay-air-sdk-flex-sdk.html> but a few alterations to this are needed to Step 4 if running on macOS. For this platform, the downloaded AIR SDK zip needs to be expanded to a temporary area and then the copy command needs to copy symbolic links as links rather than resolving them to files. This can be done using a capital ‘R’ rather than lowercase, hence:

```
cp -Rf /tmp/AIRSDK_Flex_MacOS/* /path-to-empty-FLEXSDK-directory
```

Please note that the config files (air-config.xml, airmobile-config.xml, flex-config.xml) may need to be updated to support new features and updates in AIR or in dependencies such as ANEs. For example to ensure the correct SWF version is output, the below line would need to be updated (e.g. to ‘50’ for AIR 50.x, or ‘44’ for AIR 33.1, etc):

```
<swf-version>14</swf-version>
```

3 Summary of changes

3.1 Runtime and namespace version

Namespace: 51.4

SWF version: 51

There are no new ActionScript APIs but the application descriptor file format has been updated to include support for an Android “r8” entry – see “Github-4331” section below. The new namespace version is 51.4.

For more details, see the sample application descriptor, as well as the XML schema definition documents, that are provided within the AIR SDK.

3.2 Build Tools

The Android build tools and platform used to create the AIR runtime files are Android-36 with the default target SDK also set to this level in the generated Android manifest files.

Xcode 26.5, macOS SDK 26.5 and iPhoneOS/tvOS SDK 26.5 were used to build the AIR SDK. This does not impact the IPAs generated by the AIR SDK which should satisfy the latest Apple App Store requirements. The minimum supported OS version for iPhoneOS/tvOS is now 13.0 due to the support of the scene lifecycle.

The build system for this is on a version of macOS that doesn't support 32-bit processes hence we cannot generate the 32-bit versions of the stub files. This means that we can no longer support older 32-bit iPhone/iPad devices.

3.3 AS3 APIs

No changes.

3.4 Features

Reference:	AIR-8042
Title:	Expose thread/mutex VMPI methods via ANE interface
Applies to:	All runtime components
Description:	The interface for AIR Native Extensions has been updated to provide some utility typedefs and methods for handling multi-threading and mutex objects from within an ANE. These methods are based on – and implemented by – the “Virtual Machine Porting Interface” used by the ActionScript virtual machine (avmplus). For more details, see the header files “FlashRuntimeExtensions.h” within the “include” folder in the SDK.

Reference:	Github-4290 - https://github.com/air sdk/Adobe-Runtime-Support/issues/4290
Title:	Updating default purpose strings for iOS apps
Applies to:	Core build tools
Description:	The original “Required by Apple” purpose strings, intended to provide information to users when an application needs a particular iOS feature, were being blocked by App Store reviews as being too short/generic. Some extended strings have been added instead which we believe will be allowed, at least in the short term. Alternatively developers can add bespoke values for their application via the InfoAdditions mechanism.

Reference:	Github-4323 - https://github.com/air sdk/Adobe-Runtime-Support/issues/4323
Title:	Adding basic minify/obfuscation support for Android
Applies to:	Core build tools
Description:	In order to support forthcoming requirements around code obfuscation and minification for the Android Play Store, ADT has been updated to provide a proguard file that configures the Android Gradle Plug-in to ensure some minification and obfuscation occurs. This is at a basic level which needs to exclude a lot of the Adobe runtime classes due to the heavy use of JNI calls from C++ into Java, as well as some reflection within the Java classes themselves. See also the Github-4331 updates below.

Reference:	Github-4329 - https://github.com/air sdk/Adobe-Runtime-Support/issues/4329
Title:	Updating IPA MinimumOSVersion to 13.0
Applies to:	Core build tools
Description:	This update within ADT means that IPA files generated by the AIR SDK will have a minimum target OS version of 13.0. Applications can configure a higher MinimumOSVersion for themselves using the app descriptor file (in the InfoAdditions section), and the value could be increased by a flag within an ANE platform extension descriptor file, but 13.0 is now the minimum. See also the Github-4333 updates below.

Reference:	Github-4331 - https://github.com/air sdk/Adobe-Runtime-Support/issues/4331
Title:	Adding app descriptor settings for Android Proguard configurations
Applies to:	Core build tools
Description:	Along with the built-in ADT proguard file, there is now support within the application descriptor for an “r8” section that can be used to enable and disable the minification/obfuscation feature, and to provide additional rules files that should be included in the proguard settings within the build process. Multiple files can be provided, and the filenames may be relative (typically to the location of the application descriptor file). If the files can’t be found, an error will be output for the build, as this invalidates the application descriptor file. The files are only used at built-time and are not deployed with the compiled application (i.e. are not present in the generated AAB/APK files). The updates to the app descriptor XML format can be seen within the 51.4 XSD file provided with the SDK, and these will also be updated online. Default for the enablement flag is currently ‘false’ because so many classes are excluded (due to being called from JNI) that not much improvement is gained from this feature, at least on a test app.

Reference:	Github-4333 - https://github.com/air sdk/Adobe-Runtime-Support/issues/4333
Title:	Scene lifecycle and storyboard-based AIR runtime
Applies to:	iOS runtime component
Description:	A significant update has been made to move AIR into a storyboard-based application. This work was done alongside the changes to make the apps comply with the scene lifecycle, although AIR apps are essentially simple single-scene applications, so the appropriate scene details are created automatically within the target app’s Info.plist file. Whilst these changes have been tested across a number of test apps and devices, they are relatively significant and so if any issues are found with this mechanism, we would be grateful for quick and detailed feedback.

3.5 Bug Fixes

3.5.1 Release 51.4.1.1

Reference:	AIR-8037
Title:	Add synchronization to SecureSocket thread handling
Applies to:	Android runtime component
Description:	An error had been raised with crashes seen within the AndroidSecureSocket class that appeared to be caused by null pointer dereferencing within secondary threads and callbacks. To avoid these issues, a synchronisation object is used to ensure that the main Android socket object is always kept valid for the duration of any callback or asynchronous operation, which should eliminate these crashes.

Reference:	AIR-8038
Title:	Adding exception handling around external interrupt handler
Applies to:	All runtime components
Description:	Several crash reports showed an issue caused when an 'external interrupt' had been triggered somehow: the handler for this had tried to throw an exception object into the AS3 runtime, but the AS3 handler then threw its own exception, and the original call did not have try/catch protection. This has been updated, with any error happening during this scenario now being fed into the 'unhandled exceptions' process/handler.

Reference:	Github-4292 - https://github.com/airSDK/Adobe-Runtime-Support/issues/4292
Title:	Ensure windows ALT keyDown event can have default behaviour prevented
Applies to:	Windows runtime component
Description:	If the 'alt' key was pressed/released on its own, it would steal focus from the AIR application, despite not fully activating the window's system menu. To capture and avoid this issue, there is now the option of handling the AS3 keyDown event for this key code, and calling "preventDefault()" on the event object. This then prevents the Windows event from being passed into the default window process, which means focus remains with the AS3 app.

Reference:	Github-4310 - https://github.com/airSDK/Adobe-Runtime-Support/issues/4310
Title:	Updating Mac webview to send location events and fix location/title properties

Applies to:	macOS runtime component
Description:	The new macOS WebView implementation had a logic issue whereby the location events weren't being sent at all due to the incorrect setting of a flag. This flag is now being correctly reset at the start of navigation. Additionally, a request for the page title was causing an unknown selector failure due to some of the legacy code not having been correctly updated; this has also been fixed so that the new implementation's page title is correctly retrieved from the platform's WKWebView instance.

Reference:	Github-4325 - https://github.com/airSDK/Adobe-Runtime-Support/issues/4325
Title:	Ensuring windows mousewheel events happen on each click of the wheel
Applies to:	Windows runtime component
Description:	When the change was made recently to ensure touch-pad gestures would trigger mouse wheel events, a cumulative 'distance moved' was used along with a threshold beyond which an event would be sent. The threshold used the Windows constant for a mousewheel rotation unit – but the comparison was “greater than”, and this meant that a single rotation unit of a mouse wheel was not triggering the AS3 event. The comparisons have been updated so that they also trigger on “equal to”.

Reference:	Github-4332 - https://github.com/airSDK/Adobe-Runtime-Support/issues/4332
Title:	Correcting the Android build-tool binaries back to 36.0.0
Applies to:	Android runtime component
Description:	In the latest release, the Android “aapt” and “d8.jar” tools had been accidentally reverted to earlier versions due to an old build script; these have been corrected back to the versions from 36.0.0.

4 Configuration File

ADT uses an optional configuration file to change some of its behaviour. To create a configuration file (there is not one by default within the SDK), create a new text file and save this with the name “adt.cfg” in the SDK’s “lib” folder (i.e. alongside the ‘adt.jar’ file). The configuration file is in the standard ‘ini file’ format with separate lines for each option, written as “setting=value”. Current options are listed below:

Setting	Explanation
DefaultArch	Used as a default architecture if there is no “-arch” parameter provided to ADT. Values may be ‘armv8’, ‘armv8’, ‘x86’ or ‘x64’.
OverrideArch	Used where an architecture value is being provided to ADT using the ‘-arch’ parameter, this configuration setting will override such parameter with the value given here. Values may be ‘armv8’, ‘armv8’, ‘x86’ or ‘x64’.
DebugOut	If set to “true”, results in additional output being generated into a local file which can aid in debugging problems within ADT (including the use of third party tools from the Android SDK). Values may be ‘true’ or ‘false’, default is ‘false’.
UncompressedExtensions	A comma-separated list of file extensions that should not be compressed when such files are found in the list of assets to be packaged into the APK file. For example: “UncompressedExtensions=jpg,wav”
AddAirToAppID	Configures whether or not the “air.” prefix is added to an application’s ID when it is packaged into the APK. Values may be ‘true’ or ‘false’, default is ‘true’.
JavaXmx	Adjusts the maximum heap size available to the Java processes used when packaging Android apps (dx/d8, and javac). Default value is 1024m although this is automatically overridden by any environment variable or value passed to the originating application. If this config setting is present, e.g. ‘2048m’, then it takes priority over all other mechanisms.
CreateAndroidAppBundle	Overrides any usage of ADT with an APK target type, and instead generates an Android App Bundle. Note that the output filename is not adjusted so this may result in generation of a file with “.apk” extension even though it contains an App Bundle. Values may be ‘true’ or ‘false’, default is ‘false’.

KeepAndroidStudioOutput	When generating an Android App Bundle, rather than using a temporary folder structure and cleaning this up, this option will generate the Android Studio file structure under the current folder and will leave this in place). Values may be 'true' or 'false', default is 'false'.
AndroidPlatformSDK	A path to the Android SDK, that can be used instead of the "-platformsdk" command line parameter. Note that on Windows, the path should contain either double-backslashes ("c:\\folder") or forwardslashes ("c:/folder").
iOSPlatformSDK	A path to the iOS/iPhone/iPhoneSimulator SDK, that can be used instead of the "-platformsdk" command line parameter.
JAVA_HOME	This can be set as an override or alternative to the system environment variable that is read when ADT needs to use Java (e.g. when creating an Android App Bundle). Note that on Windows, the path should contain either double-backslashes ("c:\\folder") or forwardslashes ("c:/folder").
UseNativeCodesign	On macOS, this will mean that the IPA binary is signed using the "codesign" process rather than using internal Java sun security classes within ADT. This is "false" by default, unless ADT detects that the sun security Java classes are not available.
SignSwiftFiles	By default, any swift libraries that are included in an IPA payload are signed in the normal way. This can be turned off by setting this value to "false".
OnlyIncludeSwiftUsedArchsInSupport	If this is set to "true" then for ipa-app-store builds that include a "SwiftSupport" folder, the swift libraries will be updated via lipo to only include architectures that are used by the application (e.g. armv7 and arm64, omitting armv7s and arm64e).
OnlyIncludeSwiftUsedArchsInPayload	This is similar to the above flag but applies to the versions of the swift libraries that are included in the "Payload" folder within the IPA package. This (and the above) are now defaulting to "false" so that the swift libraries are just copied into position, but to get the legacy behaviour this should be set to "true".
iosSimulator	The name of a simulator to use when installing or running an IPA file on an iPhone simulator on mac. Note that this value will be overridden by any command-line option or by an environment variable should this be set as well (i.e. AIR_IOS_SIMULATOR_DEVICE).

IPASymbolFile	To aid in debugging iPhoneOS/tvOS issues, this setting has been introduced which should give the filename of a symbol file that will be generated as part of the iOS build process. This isn't a human-readable file, but if a crash log is produced from an AIR application on iOS/tvOS, this file can be provided to HARMAN along with the crash log in order for us to investigate the crash location and call stack.
LLVM_HOME	[Windows only, currently] Specifies the installation directory for the LLVM toolchain. If this entry is present, ADT will use the LLVM linker called "ld64.lld.exe" situated in the "bin" folder of the LLVM_HOME location. When switching to the LLVM implementation of the linker, it is then possible to use the "iOSPlatformSDK" setting (or the "-platformsdk" command-line argument to reference the actual Apple iPhoneOS SDK which means linking will take place against the "TBD" files, and Apple's newer dynamic linking/loading mechanisms should then work across the different iOS versions. This mechanism should result in more stable binaries than when linking against the "stub" SDK files provided in the AIR SDK. These stub files will be removed in the future, with LLVM becoming the standard mechanism for linking on non-macOS platforms.
PackageValidation	Whether or not the application should validate the package contents at start-up. With AIR 51.2, license files include information about the package that is created by ADT, and the runtimes will validate that these have not been significantly tampered with. This check can be disabled if this flag is set to "never" – default is "always". Note that from 51.2.2.4 it's also possible to use the options "true" (to always validate) or "false" (to never validate). In future we may change how this flag works e.g. for only specific applications, or for only debug-type packages. Note that from 51.3.3.2 an additional option "disable" has been provided, which is similar to "never" but makes the overall mechanism a lot more robust and able to cope with post-processing operations that could have updated the application descriptor or identifier.
VerboseOut	Similar to "DebugOut" but this option will provide a lot more information to the output log / troubleshooting page. If this is set to "true", it will ignore the setting of "DebugOut" which would be set on implicitly.

UseXcodeForIPAConstants	From 51.3.3.1, this flag can be used to turn off the feature where ADT checks the Xcode installation on macOS to determine the version numbers/codes to use within the property list of an IPA file. If the flag is missing, or “true”, then ADT will continue to check via Xcode and will pick up the values from the devices on which the build is running. If the flag is set to “false”, then ADT will use the internal hard-coded values, to match the behaviour that is used on Windows machines.
-------------------------	--

5 Android builds

5.1 AAB Target

Google introduced a new format for packaging up the necessary files and resources for an application intended for uploading to the Play Store, called the Android App Bundle. Information on this can be found at <https://developer.android.com/guide/app-bundle>

AIR now supports the App Bundle by creating an Android Studio project folder structure and using Gradle to build this. It requires an Android SDK to be present and for the path to this to be passed in to ADT via the “-platformsdk” option (or set via a config file – it also checks in the default SDK download location). It also needs to have a JDK present and available, and will attempt to find this either from configuration files or via the JAVA_HOME environment variable (or if there is an Android Studio installation present in the default location, using the JDK provided by that).

To generate an Android App Bundle file, the ADT syntax is similar to the “apk” usage:

```
adt -package -target aab <signing options> output.aab <app descriptor and files> [-extdir  
<folder>] -platformsdk <path_to_android_sdk>
```

No “-arch” option can be provided, as the tool will automatically include all of the architecture types. Signing options are optional for an App Bundle.

Note that the creation of an Android App Bundle involves a few steps and can take significantly longer than creating an APK file. We recommend that APK generation is still used during development and testing, and the AAB output can be used when packaging up an application for upload to the Play Store.

ADT allows an AAB file to be installed onto a handset using the “-installApp” command, which wraps up the necessary bundletool commands that generate an APKS file (that contains a set of APK files suitable for a particular device) and then installs it. If developers want to do this manually, instructions for this are available at https://developer.android.com/studio/command-line/bundletool#deploy_with_bundletool, essentially the below lines can be used:

```
java -jar bundletool.jar build-apks --bundle output.aab --output output.apks --connected-  
device
```

```
java -jar bundletool.jar install-apks --apks=output.apks
```

Note that the APK generation here will use a default/debug keystore; additional command-line parameters can be used if the output APK needs to be signed with a particular certificate.

5.2 Play Asset Delivery

As part of an App Bundle, developers can create “asset packs” that are delivered to devices separately from the main application, via the Play Store. For information on these, please refer to the below link:

<https://developer.android.com/guide/playcore/asset-delivery>

In order to create asset packs, the application XML file needs to be modified within the <android> section, to list the asset packs and their delivery mechanism, and to tell ADT which of the files/folders being packaged should be put into which asset pack.

For example:

```
<assetPacks>
```

```
<assetPack id="ImageAssetPack" delivery="on-demand"
folder="AP_Images"/>
</assetPacks>
```

This instruction would mean that any file found in the "AP_Images" folder would be redirected into an asset pack with a name "ImageAssetPack". The delivery mechanisms can be "on-demand", "fast-follow" or "install-time" per the Android specifications.

Note that assets should be placed directly into the asset pack folder as required, rather than adding an additional "src/main/assets" folder structure that the Android documentation requires. This folder structure is created automatically by ADT during the creation of the Android App Bundle.

The asset pack folder needs to be provided as a normal part of the command line for the files that should be included in a package. So for example if the asset pack folder was "AP_Images" and this was located in the root folder of your project, the command line would be:

```
adt -package -target aab MyBundle.aab application.xml MyApp.swf AP_Images
[then other files, -platformsdk directive, etc]
```

If there were a number of asset packs and all of the relevant folders were found under an "AssetPacks" folder in the root of the project, the command line would be:

```
adt -package -target aab MyBundle.aab application.xml MyApp.swf -C
AssetsPacks . [then other files, -platformsdk directive, etc]
```

To access the asset packs via the Android Asset Pack Manager functionality, an ANE is available via the AIR Package Manager tool. See <https://github.com/airsdk/ANE-PlayAssetDelivery/wiki>

5.3 Android Text Rendering

Previously, the rendering of text on Android had been handled via a native library built into the C++-based AIR runtime file. This had some restrictions and issues with handling fonts, which caused major problems with Android 12 when the font fallback mechanism was changed and the native code no longer coped with this. To resolve this, a new text rendering mechanism has been implemented that uses public Android APIs in order to set up the fonts and to render the text.

The new mechanism uses JNI to communicate between the AIR runtime and the Android graphics classes for this, and has some differences with the legacy version. One of the changes that has been made is to correct the display of non-colored text elements when rendering to bitmap data: in earlier builds, if some text included an emoji with a fixed color (e.g. "flames" that are always yellow/orange even if you request a green font color) then these characters appeared blue, due to the different pixel formats used by Android vs the AIR BitmapData objects. With the new mechanism, AIR correctly renders these characters to BitmapData (although the problem still remains when rendering device text to a 'direct' mode display list).

Some developers may not want to switch to this new mechanism yet, and others may want their applications to always use it. Some would perhaps want it only when absolutely necessary i.e. from Android 12 onwards. To cope with this request, there is a application descriptor setting that can be used: "<newFontRenderingFromAPI>" which should be placed within the <android> section of the descriptor XML. The property of this can be used to set the API version on which the new rendering mechanism takes place. The default value is API level 31 which corresponds to Android 12.0 (see <https://source.android.com/setup/start/build-numbers>). So for example if you always want devices to use the new mechanism, you can add:

```
<newFontRenderingFromAPI>0</newFontRenderingFromAPI>
```

whereas if you never want devices to use this, you could add:

```
<newFontRenderingFromAPI>99999</newFontRenderingFromAPI>
```

5.4 Android File System Access

In the earlier versions of Android, it was possible to use the filesystem in a similar way to a Linux computer, but with a set of restrictions that had a fairly high-level granularity:

- It was possible to read/write to an application's private storage location. AIR exposes this via `"File.applicationStorageDirectory"`.
- If the app requested the 'read/write storage' permission, the app could then read and write in the user's shared storage location and to removable storage. The main home folder was accessible via `"File.userDirectory"` or `"File.documentsDirectory"`, and later AIR 33.1 added `"File.applicationRemovableStorageDirectory"`.
- Later, this was updated such that the user had to also grant permission via a system pop-up message. To trigger this pop-up, AIR developers could use `"File.requestPermission()"`

With the introduction of "scoped storage" however, a lot of this has changed. Android files are treated in a similar way to other resources, with URLs using the `"content://"` schema which can refer either to filesystem-backed files, or to transient resources, or elements within other storage mechanisms such as databases and libraries. Permission to access each resource depends upon the creator of that resource, and by default it's not possible for an application to open a file that another application had created. Permissions for the top-level internal storage (i.e. `"File.documentsDirectory"`) have been changed so that applications cannot create entries here but must use sub-folders of these (a set of standard sub-folders is generally created by the OS).

Within AIR, we have been attempting to add support for the `"content://"` URLs, and to switch the File class `"browseForXXX"` functions so that they use the new intent-based mechanisms for selecting files to open and save, or to select a folder. Within these calls, we are also requesting the appropriate read/write permissions (and persisting these so that they can be used in the future). This means that it should be possible to call `"browseForOpen()"` and allow the user to select a shared file that can then always be opened (for reading). Equally a `"browseForDirectory()"` call should mean that an application then has read/write access into the selected directory and its sub-tree.

Requesting file system permissions has to be handled in a similar way, with permissions either granted for a file or for a folder tree. The `"File.requestPermission()"` function therefore looks at the native path of the File object this is called on, and decides whether to show a file open intent (if there's a normal path or URL in the `nativePath` property), or to show a folder selection intent (if the path ends in a forward-slash), or whether to just ignore the call with a 'granted' response and then wait for later permission requests for individual files (if the File object has not had a `nativePath` set). This last option is intended to allow apps to work across different Android versions and is the recommended option: early in the application lifecycle, create a new File and call `requestPermissions()`: if the app is running on an earlier Android version, the permission pop-up will appear, otherwise the app will need to request specific file access later on via the `"browseForXXX"` functions or by requesting permission for a specific file. Sadly it isn't possible to ensure that the user only gives a yes/no response for these file/folder open intents, they are able to browse for other files, so it may be that the file the user selects is not the one you are trying to open. If this is detected, the permission status event will show as 'denied', so if you are happy for the user to choose a different file, use `"browseForOpen()"` rather than `"requestPermission()"`.

There is an exception to having to use scoped storage and the storage access framework, which is if an application has the `"MANAGE_EXTERNAL_FILES"` permission. This permission is intended for utilities such as file manager apps and anti-virus scanners that have a legitimate need to access all the (shared storage) files on the device, but if an app requests this permission and is submitted to the Play Store, but doesn't justify itself, then the submission is likely to be rejected.

Some applications are not distributed via the Play Store though, at which point this permission can be used to turn the behaviour back to how it used to be in earlier Android versions. The



“`File.requestPermission()`” capability has been overridden in the cases where AIR detects this permission has been requested in the manifest, and it will now display the appropriate dialog to ask the user to turn on the ‘all files’ access for this app. Once this has been granted (asynchronously), it would then be possible to create, read and write files and folders including in the root storage device.

6 Windows builds

The SDK now includes support for Windows platforms, 32-bit and 64-bit. We recommend that developers use the “bundle” option to create an output folder that contains the target application. This needs to be packaged up using a third party installer mechanism, in order to provide something that can be easily distributed to and installed by end users. HARMAN are looking at adapting the previous AIR installer so that it would be possible for the AIR Developer Tool to perform this step, i.e. allowing developers to create installation MSI files for Windows apps in a single step.

Instructions for creating bundle packages are at:

https://help.adobe.com/en_US/air/build/WSfffb011ac560372f709e16db131e43659b9-8000.html

Note that 64-bit applications can be created using the “-arch x64” command-line option, to be added following the “-target bundle” option.

7 MacOS builds

MacOS builds are provided only as 64-bit versions. A limited shared runtime option is being prepared so that existing AIR applications can be used on Catalina, but the expectation for new/updated applications is to also use the “bundle” option to distribute the runtime along with the application, as per the above Windows section.

Note that Adobe’s AIR 32 SDK can be used on Catalina if the SDK is taken out of ‘quarantine’ status. For instructions please see an online guide such as:

<https://www.soccertutor.com/tacticsmanager/Resolve-Adobe-AIR-Error-on-MacOS-Catalina.pdf>

AIR SDK now supports MacOS Big Sur including on the new ARM-based M1 hardware: applications will be generated with ‘universal binaries’ and most of the SDK tools are now likewise built as universal apps.

8 iOS support

8.1 32-bit vs 64-bit

For deployment of AIR apps on iOS devices, the AIR Developer Tool will use the provided tools to extract the ActionScript Byte Code from the SWF files, and compile this into machine code that is then linked with the AIR runtime and embedded into the IPA file. The process of ahead-of-time compilation depends upon a utility that has to run with the same processor address size as the target architecture: hence to generate a 32-bit output file, it needs to run a 32-bit compilation process. This causes a problem on MacOS Catalina where 32-bit binaries will not run.

Additionally, due to the generation of stub files from the iPhone SDK that are used in the linking process – which are created in a similar, platform-specific way – it is not possible to create armv7-based stub files when using Catalina or later. From release 33.1.1.620, the stub files are based on iOS15 and are purely 64-bit. This means that no 32-bit IPAs can be generated, even when running on older macOS versions or on Windows.

8.2 MacOS remote linking from Windows

Due to a number of updates from Apple around the mach-o linker, and the movement of symbols between different component libraries, it has become increasingly problematic to link Apple binaries on a Windows computer. Originally, Adobe had cross-compiled the “ld64” Apple linker, but without support for the “TBD” format that Apple use for the iPhoneOS/AppleTVOS SDKs. To work around this limitation, the AIR SDK includes “stub” binaries for the SDKs – but it is not then possible to support the movement of symbols i.e. where a particular symbol is found in different frameworks for different iOS versions.

Using LLVM’s linker, which supports the mach-o format, it was also found that Apple restrictions had been preventing some applications from being published via the App Store due to a difference in how symbols were found/stored, and the known/unsupported issues in LLVM meant that this is also not a completely viable solution.

The solution that we will work with now is to use a mac machine to perform the link stage of the build process. The rest of the development and build process can still occur on Windows but linking the AIR application’s object files against the iPhone / AppleTV SDKs should be done on a mac.

There are two ways to achieve this: initially a manual mechanism to allow files to be pushed to a macOS machine, linked via a script, and then the result copied back to the Windows machine where the packaging command needs to be run again to pick up the binary. And with the release of 51.0.1 this is now possible to handle automatically within a single run of ADT, following some initial machine configuration. Details on these two methods follow.

8.2.1 Manual copying and linking

There are a number of steps to the build process in this scenario.

1. Configure ADT to use a specific folder, into which all linker inputs will be placed.

To do this, edit the “adt.cfg” file (in your home folder under an “.airsdk” subfolder) and add a line: “IPALinkFolder=c:/path/to/link/folder”. This must be the name of an existing folder, under which subfolders will be created for each run of ADT. Note that you need to use forward-slashes, or escaped backslashes (“\\”), due to how Java reads in property files.

2. Run your normal link command via ADT.

This will then generate a subfolder under your “IPALinkFolder” location, which contains a script file and all the input files needed for the Apple linker.

3. Copy this link folder to your macOS computer.

This can be done with SFTP/SCP or similar tools, or potentially you could have a network shared folder set up.

4. On the macOS computer, run the linker.

Using a terminal window, you will first need to set an environment variable, "AIR_SDK_HOME", and then run the script that was generated by ADT. For example:

```
export AIR_SDK_HOME=/Users/username/Downloads/AIR_SDK/AIRSDK_51.0.1  
./linkerscript.sh
```

5. Copy the resulting file back onto the Windows PC.

The file should be called "linkerOutput" and should be an arm64 macho executable file.

6. Call ADT again, this time providing the linked file.

To do this, add the arguments "-use-linker-output path_to_linkerOutput"; this can go within the normal input files list, or at the end of this (similar to "-extdir").

ADT will then ignore the normal command to link the binary, and will use the provided executable in order to package and sign the IPA file.

7. Clean up.

The folder that's created under the "IPALinkFolder" location, as well as the linkerOutput file (and of course the files that have been copied to the macOS machine) are not automatically deleted. So these should be periodically cleaned up manually to avoid wasting disk space.

8.2.2 Programmatic remote linking

In order to automatically allow the Windows machine to connect to the macOS machine and to copy files and drive the linker, a password-less mechanism will need to be set up to allow remote access without any user interaction. This requires the use of SSH keys: unless a key-pair is created that doesn't have a passphrase, it will be necessary to use "ssh-agent" to store the passphrase and associate this with the user's Windows credentials.

To set this up (one time only):

1. Create a new key-pair (unless you want to use an existing pair).

On Windows, run "ssh-keygen" and provide a filename – the default is "id_rsa" but in this walkthrough we shall use "adt_access". It then prompts for a passphrase: if you leave this blank, you will not need to follow the "ssh agent" steps below, but the recommendation would be to create a suitably secure passphrase for this. You should then have two files, "adt_access" and "adt_access.pub".

2. Install the public key on the mac machine.

You can use sftp/scp for this. The key should be added into your ".ssh" folder – note that you need the username of the mac machine, which we shall assume is just "user". You will then need to configure SSH to allow this public key to be used for connections: if you remote in (or just open a terminal) on the mac, go into the ".ssh" folder, and run: "cat adt_access.pub >> authorized_keys". This adds the new key onto the end of the authorized keys list.

3. Set up ssh agent to provide the passphrase.

Firstly you will need to check that ssh-agent is running: open "Services" on the computer, and find an entry with name "OpenSSH Authentication Agent". This should be changed to "Automatic", or "Automatic (Delayed Start)" if you prefer, and if necessary, also started manually. The "Status" column should show that this is running.

Then in a Windows console, run “ssh-add adt_access” and provide your passphrase.

Note that if you get an error message “Permissions for 'private-key.ppk' are too open”, you will need to ensure that only the current user is able to access the private key file (“adt_access”). This means adjusting the “Security” properties on this file, changing the owner of the file to the current local user account, removing inheritance and inherited permissions, and removing all permissions for users/groups other than the current local user. For more details, see the below link:

[Windows SSH: Permissions for 'private-key' are too open - Super User](#)

You can then test the connection by running “ssh -i adt_access user@mac_ip_address”, which should then log on automatically without further prompting.

4. Provide the configuration to ADT.

Now that you have the connectivity set up, you need to create a configuration file for AIR. You will need to add two entries into the “adt.cfg” file that is in your “c:\users\username\.airsdk\” folder:

```
IPALinkFolder=c:/path/to/link/folder  
RemoteLinkMachine=mac_ip_address
```

The first setting is to provide a location into which the linker will output all of the files. This is not strictly necessary but will aid in debugging problems.

The second provides the network location of the remote machine onto which you've put the public ssh key.

You will then need to create a configuration file with the name of this “mac_ip_address” network address, with an “.cfg” extension, and put this into a subfolder “remote_link_configs” under the .airsdk directory. For example:

```
C:\Users\username\.airsdk\remote_link_configs\192.168.1.3.cfg
```

The contents of this file should be:

```
CertPath=C:/path/to/private/key/adt_access  
Username=user  
SdkFolder=/Users/user/Documents/AIR_SDKs/AIRSDK_51.0.1
```

The “CertPath” value points to the private key that we've named “adt_access”, again please note the use of forward-slashes or double-backslashes in the Windows path. “Username” is the user associated with the key from when this was added to “authorized_keys”. And “SdkFolder” is the path on the remote mac machine where an AIR SDK can be found. This path is only used for the runtime libraries i.e. “libRuntimeHMAOT.arm-air.a” and “builtin_abc.arm64-air.o”, the linker won't use this for the actual link binary (ld64) or the stub files; instead, the remote script picks up your iPhoneOS SDK using the “xcrun” utility.

Once that is all set up, you can use ADT as normal for IPA builds, and the remote linking will happen in the background. If there are issues, please check the adt.log (or use AIR SDK Manager's “Troubleshooting” tab) and report an issue via Github.

Please do note that the link folders are not (currently) cleaned up with this approach, so the location under the “IPALinkFolder”, and its copy that is pushed to the remote Mac device (with the same name, within the user's home folder) will still exist after the ADT process has completed. This will help with debugging any issues, but we expect to change this in the future.

9 Splash Screens

For our 'free tier' users, a splash screen is injected into the start-up of the AIR process, displaying the HARMAN and AIR logos for around 2 seconds whilst the start-up continues in the background. There are different mechanisms used for this on different platforms, the current systems are described below.

9.1 Desktop (Windows/macOS)

Splash screens are displayed in a separate window centred on the main display, while the start-up continues behind these. The processing of ActionScript is delayed until after the splash screen has been removed.

9.2 Android

The splash screen is displayed during start-up and happens immediately the runtime library has been loaded. After a slight delay the initial SWF file is loaded in and when processing for this starts, the splash screen is removed.

9.3 iOS

The splash screen is implemented as a launch storyboard with the binary storyboard and related assets included in the SDK. This has implications for those who are providing their own storyboards or images in an Assets.car file:

- If you are on the 'free tier' then the AIR developer tool will ignore any launch storyboard you have specified within your application descriptor file, or provided within the file set for packaging into the IPA file.
- If you are creating an Assets.car file, then you need to add in the AIR splash images from the SDK which are in the "lib/aot/res" folder. These should be copied and pasted into your ".xcassets" folder in the Xcode project that you are using for creation of your assets.

Troubleshooting:

Message from ADT: "warning: free tier version of AIR SDK will use the HARMAN launch storyboard" – this will be displayed if a <UILaunchStoryboardName> tag has been added via the AIR application descriptor file. The tag will be ignored and the Storyboard from the SDK will be used instead.

Message from ADT: "warning: removing user-included storyboard "[name]" will be displayed if there was a Storyboardc file that had been included in the list of files to package: this will be removed.

Message from ADT: "warning: free tier version of AIR SDK must use the HARMAN launch storyboard" – this will be displayed if the Storyboardc file in the SDK has been replaced by a user-generated one.

If a white screen is shown during start-up: check that the HARMAN splash images are included in your assets.car file. Note that the runtime may shut down if it doesn't detect the appropriate splash images.

The runtime may also shut down for customers with a commercial license if a storyboard has been specified within the AIR descriptor file but not added via the list of files to package into the IPA file.

10 AIR Diagnostics

10.1 Purpose

The goal of the AIR diagnostics implementation is to allow both developers and HARMAN to benefit from additional metrics around an application for debugging purposes. One of the key goals is to allow errors that occur in the field to be detected and reported back, with an initial focus being around the Android "Application Not Responding" issues that are relatively common and can trigger the 'bad behaviour' labels from the Google Play Store.

There have also been a number of situations where HARMAN are unable to reproduce issues, and where additional logging has been added to the AIR runtime for developers to then reproduce a problem and report back. With the framework in place for AIR diagnostics, such logging could then start using this mechanism, and could then be left in place and become part of the generic runtimes rather than needing customer-specific builds.

10.2 Mechanism

Implementing a mechanism to capture diagnostics has to also consider the performance of the runtime, as we do not want to significantly impact performance (or memory footprint) of the deployed applications. It is important therefore that any checks as to whether a particular diagnostic should be captured/reported should be as minimal as possible, and no processing of data specific to this should occur if the relevant category of diagnostic has not been enabled.

Internally, we have used ANEs as the basis of the mechanism to enable the diagnostics, to select which categories to enable, and to receive feedback from the runtime. The ANE native implementation is built into the runtime, but needs to be enabled through the inclusion of an ANE, or more accurately a SWC library that provides the API for this and that then communicates with the runtime.

To enable diagnostics then, an application will need to add the extension ID to their application descriptor file: "com.harman.air.AIRDiagnostics". The application can then configure the diagnostics to specify a reporting folder, or to check for existing reports left from previous runs of the application, or to get more details on a report. It can add listeners for feedback for particular situations and can configure the categories of diagnostics that it wants to listen for.

The standard case for diagnostics should be that the AIR runtime writes relevant information (asynchronously!) to log files, and these can then be interpreted to generate reports of the data. The data should be machine-readable so different structures and schemas will be defined for these as relevant. One of the benefits of using an ANE mechanism is that this can then be adapted and extended more rapidly than if we used a built-in ActionScript API (as well as keeping all of this logic outside of the runtime and only included on-demand).

Typically when the application exits, the diagnostic reports that are being generated are then removed. This obviously helps to limit the size of the storage needed for diagnostics, but also means that an application can check on start-up for the existence of a report: and if it's found, it implies that the application may have had an uncontrolled exit the last time it was used. If that was, for example, caused by an Android ANR with the OS shutting down the application, it's possible that the "long function" diagnostic may contain the clues as to the cause of this behaviour.

10.3 Categories

The number of categories will be expanded as time goes by, so this list will be kept in sync with the availability of each category within the relevant runtime version.

10.3.1 Long-running functions

ANR problems can happen if a call into the AIR runtime blocks the UI thread for too long. To try to find if there are functions that generally run for longer than expected, this category has been added to try to help identify the culprit. The functions that are tracked are:

- Processing a frame (i.e. executing all 'enter frame' type event handlers and normal frame advance behaviours)
- Rendering a frame (i.e. the drawing / graphics code)
- GC: marking non-stack roots
- GC: marking queue and stack
- GC: sweeping

Functions are checked every second to see if they are still running. This is an excessive amount of time and so will be logged. If a function subsequently completes, but takes over 2 seconds, then a notification event is sent out from the diagnostics ANE.

If the runtime is killed by the OS then a report should be available that contains information about which functions have taken a lot of time, to see if this information shows a pattern of a particular function that may have been starting to increase in duration.

10.3.2 Garbage Collection activity

This is often an area that is considered problematic particularly in the final phase of collection. AIR runs garbage collection on a frame-by-frame basis (using reference counting) as well as on a mark-and-sweep basis (using roots and finding objects that are not then reachable from these). This category focuses on the mark-and-sweep approach, and will notify of the start of an incremental marking session (meaning that some condition within the runtime has triggered the start of garbage collection), the end of incremental marking, the start and end of the final stack-based marking, and the start and end of the 'sweep' phase where object destructors are called and memory clean-up and consolidation happens. The metrics include memory usage at each stage so this may also help to see whether there had been any benefit in collection at this point, which may help inform any tweaks that may be needed to the garbage collection policy.

Note that if the final stack marking and sweeping takes too long, this will also be notified as a long-running function.

10.4 Diagnostic API and guide

At the time of writing, the API is still being finalised; this will be released shortly and the actual API and documentation will be provided at that time.

In the meantime, there is a sample application that demonstrates how the ANE can be used to request some diagnostics and check the results of this: this will be updated periodically, and the latest ANE can be downloaded from the 'ane' subfolder:

https://github.com/airsdk/Adobe-Runtime-Support/tree/master/samples/air_diagnostics

10.5 FAQs

How do I get information off the device?

Currently this will have to be done by the application logic. The API includes some ways to get at the data and this could be wrapped into calls to a back-end service. HARMAN are considering providing a service here that could receive an application's diagnostics and make this available to both the application developers and to ourselves, to help in remote debugging; however, at this point in time it would be up to the application developer to somehow detect the presence of a report and send the information somehow.

What are the privacy concerns?

We are not intending to collect customer data, or any information that could allow a specific customer to be identified. Information should be solely related to the application itself, as well as some general details about the device (OS/version/CPU/etc).

It is expected that developers will be providing a privacy policy to their end users, and this should mention the collection of information in order to improve the application or service, in order to cover the use of this diagnostics mechanism.

Why do we not just extend the capabilities of Adobe Scout?

We had considered adding additional capabilities to Scout, in particular around the memory and GC mechanisms. But the real issue is that we want to collect data from applications deployed in the field, with end users who will not have any development tools or debugging expertise. So the diagnostics system is set up to be self-contained within an application, with the end user not having to do anything themselves.

How can I request different categories for extra debugging?

If there are specific areas of concern or requirements for debugging, please raise a ticket on the Github system: <https://github.com/airsdk/Adobe-Runtime-Support/issues>

If you have an existing issue open that you believe would benefit from this approach, please add a comment to the ticket and raise this as a possibility.